















All Product Spec Sheet - Ecommerce



Effective 04/15/14

QUIETCOOL FANS	PRODUCT DESCRIPTION	PART NUMBER	MOTOR VOLTAGE	MOTOR WATTS	AIR CFM	DUCT DIA.	DUCT LGTH.	HEAD DIA.	HEAD LGTH.	SOUND LEVEL	INS. R VALUE	ROUGH OPENING	GRILL DIM.	CASE WEIGHT	CFM/WATT
	<b>CLASSIC</b> 1527 CFM FAN - 1 Speed	<b>QC CL-1500</b>	120	156	1527	14"	6'	14.5"	13 3/4"	43 db	5	14.25" X 14.25"	16" X 16"	36	9.78
	<b>CLASSIC</b> 2285 CFM FAN - 2 Speed	<b>QC CL-2250</b>	120	High 252 Low 199	High 2285 Low 1829	16"	6'	16.5"	13 3/4"	High 45 db Low 43 db	5	14.25" x 18.25"	16" X 20"	42	High 9.06 Low 9.19
	<b>CLASSIC</b> 3190 CFM FAN - 2 Speed	<b>QC CL-3100</b>	120	High 320 Low 231	High 3190 Low 1906	16"	6'	16.5"	13 3/4"	High 48 db Low 42 db	5	14.25" x 22.25"	16" x 24"	47	High 9.97 Low 8.25
	<b>CLASSIC</b> 4534 CFM FAN - 4 Speed	<b>QC CL-4500</b>	120	High 504 Low 249	High 4534 Low 2457	16"	6'	16.5"	13 3/4"	High 47 db Low 44 db	5	14.25" x 36.25"	16" x 38"	81	High 8.99 Low 9.87
	<b>CLASSIC</b> 6418 CFM FAN - 4 Speed	<b>QC CL-6400</b>	120	High 658 Low 329	High 6418 Low 3226	16"	6'	16.5"	13 3/4"	High 50 db Low 43 db	5	14.25" x 36.25"	16" x 38"	87	High 9.75 Low 9.81
	<b>CLASSIC</b> 4757 CFM FAN - 2 Speed	<b>QC CL-4700</b>	120	High 533 Low 491	High 4757 Low 3586	18"	6'	18.5"	13 3/4"	High 51 db Low 48 db	5	14.25" x 30.25"	16" x 32"	56	High 8.92 Low 7.30
QUIETCOOL FANS	PRODUCT DESCRIPTION	PART NUMBER	MOTOR VOLTAGE	MOTOR WATTS	AIR CFM	DUCT DIA.	DUCT LGTH.	HEAD DIA.	HEAD LGTH.	SOUND LEVEL	INS. R VALUE	ROUGH OPENING	GRILL DIM.	CASE WEIGHT	CFM/WATT
	<b>ENERGY SAVER</b> 1265 CFM FAN - 1 Speed	<b>QC ES-1250</b>	120	36.0	1265	16"	6'	16.5"	19"	42 db	4.2	14.25" x 18.25"	16" X 20"	22/17	35.14
	<b>ENERGY SAVER</b> 1765 CFM FAN - 1 Speed	<b>QC ES-1700</b>	120	76.8	1765	16"	6'	16.5"	19"	43 db	4.2	14.25" x 18.25"	16" X 20"	22/17	22.98
	<b>ENERGY SAVER</b> 2034 CFM FAN - 1 Speed	<b>QC ES-2000</b>	120	88.8	2035	16"	6'	16.5"	19"	44 db	4.2	14.25" x 18.25"	16" X 20"	25/17	22.92
	<b>ENERGY SAVER</b> 2850 CFM FAN - 1 Speed	<b>QC ES-2850</b>	120	177.6	2850	16"	6'	16.5"	19"	47 db	4.2	14.25" x 18.25"	16" X 20"	25/17	16.05
	<b>ENERGY SAVER</b> 5412 CFM FAN - 2 Speed	<b>QC ES-5400</b>	120	High 358 Low 179	High 5412 Low 2860	16"	6'	16.5"	19"	High 49 db Low 47 db	4.2	14.25" x 36.25"	16" x 38"	25/25/35	High 15.12 Low 15.98

QUIETCOOL FANS	PRODUCT DESCRIPTION	PART NUMBER	MOTOR VOLTAGE	MOTOR WATTS	AIR CFM	DUCT DIA.	DUCT LGTH.	HEAD DIA.	HEAD LGTH.	SOUND LEVEL	INS. R VALUE	ROUGH OPENING	GRILL DIM.	CASE WEIGHT	CFM/ WATT
	<b>3013 CFM ATTIC FAN</b> <i>Includes Thermostat</i>	<b>AFG CON-3.0</b>	120	250	3013	N/A	N/A	N/A	10"	N/A	N/A	N/A	N/A	16	12.05
	<b>1560 CFM ENERGY SAVER ATTIC FAN</b> <i>Includes Thermostat</i>	<b>AFG ES-1500</b>	120	30	1560	N/A	N/A	N/A	10"	N/A	N/A	N/A	N/A	14	52.00
	<b>1475 CFM ENERGY SAVER GARAGE FAN</b> <i>Thermostat Not Included</i>	<b>GA ES-1500</b>	120	47	1452	N/A	N/A	N/A	26"	59 db	N/A	14.25" X 14.25"	16" X 16"	24	31.03
	<b>1475 CFM ENERGY SAVER GARAGE FAN</b> <i>Includes Thermostat And Ceiling Damper Grill</i>	<b>GA ES-1500DLX</b>	120	47	1452	N/A	N/A	N/A	26"	59 db	N/A	14.25" X 14.25"	16" X 16"	26	31.03
	<b>1103 CFM FAN ENERGY SAVER WALL MOUNT</b> <i>Thermostat Not Included</i>	<b>GX ES-1100</b>	120	69	1103	N/A	N/A	18" x 18"	8"	61 db	N/A	14.25" X 14.25"	16" X 16"	24	15.99
	<b>1130 CFM FAN - FLAT ROOF w/ Curb</b> <i>Includes 2" x 6" curb for flat roofs w/ 14" duct collar</i>	<b>RM ES-1100CRB</b>	120	66	1130	14"	N/A	14.5"	N/A	48 db	N/A	14.25" X 14.25"	16" X 16"	43	17.12
	<b>2245 CFM FAN - FLAT ROOF w/ Curb</b> <i>Includes 2" x 6" curb for flat roofs w/ 16" duct collar</i>	<b>RM ES-2200CRB</b>	120	197	2245	16"	N/A	16.5"	N/A	51 db	N/A	16.25" X 16.25"	16" X 20"	48	11.40
	<b>1130 CFM FAN - FLAT ROOF</b> <i>For flat roofs without curb w/ 14" duct collar</i>	<b>RM ES-1100FLT</b>	120	66	1130	14"	N/A	14.5"	N/A	48 db	N/A	14.25" X 14.25"	16" X 16"	32	17.12
	<b>2245 CFM FAN - FLAT ROOF</b> <i>For flat roofs without curb w/ 16" duct collar</i>	<b>RM ES-2200FLT</b>	120	197	2245	16"	N/A	16.5"	N/A	51 db	N/A	16.25" X 16.25"	16" X 20"	37	11.40
	<b>1130 CFM FAN - SLOPED ROOF</b> <i>For sloped roofs 2 /12 to 5 /12 pitch w/ 14" duct collar</i>	<b>RM ES-1100SLP</b>	120	66	1130	14"	N/A	14.5"	N/A	48 db	N/A	14.25" X 14.25"	16" X 16"	34	17.12
	<b>2245 CFM FAN - SLOPED ROOF</b> <i>For sloped roofs 2 /12 to 5 /12 pitch w/ 16" duct collar</i>	<b>RM ES-2200SLP</b>	120	197	2245	16"	N/A	16.5"	N/A	51 db	N/A	16.25" X 16.25"	16" X 20"	39	11.40
	<b>HV-1000</b> <i>1104 CFM FAN - 2 Speed</i>	<b>QC HV-1000</b>	120	High 78 Low 39	High 1104 Low 552	N/A	N/A	N/A	N/A	High 62 db Low 60 db	7	13.25" X 22.25"	15" X 24"	24	High 14.15 Low 14.15